



主要连接尺寸MAIN DIMENSIONS(mm)

Fig.VK711 PN16																
口径 Size DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400
总长 L RF/BW	90	95	100	105	115	125	145	155	175	200	225	275	325	375	425	475
外圆 D	95	105	115	140	150	165	185	200	220	250	285	340	405	480	520	580
手轮 W	140	140	160	160	180	200	220	250	300	350	400	450	550	600	700	700
中心高 H	200	200	212	212	248	248	287	320	390	412	470	630	740	840	990	1100
重量 Weight(kg)	3.8	4.8	5.7	7.6	9	12	16	22	33	45	70	135	260	305	510	740
行程 Stroke	8	8	10	10	12	15	17	22	28	34	40	60	75	85	100	110
流量 Kvs(m3/h)	4.2	7.4	12	19	30	47	77	120	188	285	410	725	1140	1660	2230	2950
Fig.VK712 PN25																
口径 Size DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400
总长 L RF/BW	90	95	100	105	115	125	145	155	175	200	225	275	325	375	425	475
外圆 D	95	105	115	140	150	165	185	200	235	270	300	360	425	485	555	620
手轮 W	140	140	160	160	180	200	220	250	300	350	400	450	550	600	700	700
中心高 H	200	200	212	212	248	248	287	320	390	412	470	630	740	840	990	1100
重量 Weight(kg)	3.8	4.8	5.7	7.6	9	12	16	22	34	46	72	138	270	310	520	760
行程 Stroke	8	8	10	10	12	15	17	22	28	34	40	60	75	85	100	110
流量 Kvs(m3/h)	4.2	7.4	12	19	30	47	77	120	188	285	410	725	1140	1660	2230	2950
Fig.VK713 PN40																
口径 Size DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400
总长 L RF/BW	90	95	100	105	115	125	145	155	175	200	225	275	325	375	425	475
外圆 D	95	105	115	140	150	165	185	200	235	270	300	375	450	515	580	660
手轮 W	140	140	160	160	180	200	220	250	300	350	400	450	550	600	700	700
中心高 H	200	200	212	212	248	248	287	320	390	412	470	630	740	840	990	1100
重量 Weight(kg)	3.8	4.8	5.7	7.6	9	12	16	22	35	48	75	140	275	315	530	770
行程 Stroke	8	8	10	10	12	15	17	22	28	34	40	60	75	85	100	110
流量 Kvs(m3/h)	4.2	7.4	12	19	30	47	77	120	188	285	410	725	1140	1660	2230	2950